# 

## RL4809 transmitter Pro RL4800 Series

Part of the Hanwell RL4800 series of radio transmitters, the RL4809 is a dual channel transmitter with 2 x 4-20mA input for use internally or externally. Each unit includes a steel bracket for mounting purposes.

#### Features

- $\checkmark$  2 x 4-20mA input for pump, machine, level and door alerts
- ✓ 50,000 data readings per channel & up to 18 months battery life
- ✓ Superior performance hardware & high accuracy sensors
- ✓ Easily accessible battery
- Low power radio for long distance transmission (3km over open ground)
- ✓ Complies with RoHS, EU & WEEE directives

#### Carries CE Marking

#### **Typical Applications**

- Level measurement
- Door open/close alerts
- Machine on/off alerts

#### Always ask for a long-range signal strength test.



**Technical specification** Dimensions 110 x 80 x 35mm 200 grams Weight Power supply 3.6V AA Lithium battery Cable length 3m with bare ends (as shown in image) ABS & PC Case material Memory capacity 50,000 readings (unit will wrap when full) Clock accuracy (logging) 20 ppm @ 25°C -20°C to +65°C (non-condensing RH Instrument operating environment) range Storage Temperature -40°C to +60°C **IP** Rating IP30 Input

Input	Dual channel 4 to 20mA
Input impedance	100 ohms
Measuring frequency	Every transmit/log interval
Transmit interval	User programmable 30s-300s
Resolution	0.02mA
Accuracy	+/-1%



Product code: RL4809-434.075 (other frequencies are available)

Radio transmitter functions	
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.
Radio power	10mW
Radio range	3km over open ground
Battery life	Up to 18 months (dependent on conditions of use and instrument settings)
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Hardware required	SR2 – Smart Receiver REP – Repeater

#### Accessories

88706

AA 3.6V Lithium battery

### Manufactured by Hanwell | Ellab ( 🚊 RoHS

Version 2 - EC190194

**Disclaimer**: The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product maybe changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.