

Advanced Viewing Heads S650

Single channel UV+IR Advanced Viewing Head to be used with P650 Signal Processors with integrated display to monitor flame signals at the burner front.

Overview



S650 Viewing Heads are used with P650 Signal Processors. Dual UV+IR sensor technology offers flexibility to meet a wide array of applications. The sensors are not adversely affected by X-Rays and Gamma rays during operation making them ideal for monitoring all fuel flames and single or multiple burners firing multiple fuels.

Features & Benefits:

- Best in Class Dual UV+IR sensor technology offers high sensitivity, better discrimination to ensure application flexibility
- All models include electronic check for self-check of the system
- Numeric two-digit display for each sensor on the back of the Viewing Head provides UV and IR flame count.
- Quick Disconnect (order cable assembly ASY55XBE separately) for Div 2 / Zone 2 or Field Wireable models for Div 1 / Zone 1 available.
- Mountable in any orientation.
- Includes inbuilt temperature sensor.
- In Built Purge Adaptor with provision for cooling Air Inlet.

Filters

▼ CATEGORY

☒ Base Part

▼ TYPE

☒ Viewing Head

🔍 Search



Part Number	S650BE
Description	ADV. VIEWING HEAD QCK. DISCNNCT. DIV2/Z2
Category	Base Part
Type	Viewing Head
	Order Online
Part Number	S650FW
Description	ADV. VIEWING HEAD CABLE ENTRY DIV1/Z1
Category	Base Part
Type	Viewing Head
	Order Online

Rows 10 ▾

Product Number



Please sign in to view part numbers available for purchase based on your account

[Sign In](#)

S650BE
ADV. VIEWING HEAD QCK. DISCNNCT. DIV2/Z2

S650BE
ADV. VIEWING HEAD QCK. DISCNNCT. DIV2/Z2

S650FW
ADV. VIEWING HEAD CABLE ENTRY DIV1/Z1

S650FW
ADV. VIEWING HEAD CABLE ENTRY DIV1/Z1

